



# GFE-ZEOS-PROGRAMMER

## Portable Programmer

This device was designed to program ZEOS detectors made by GFE – Global Fire Equipment SA.

### LED Status

**Green** – Programmer is working correctly

**Yellow** – Operation in progress

**Red** – Electric voltage on device is above correct value

**Red Flashing** – Battery needs to be charge

### Operation

- OK** -> Power ON
- OK (2 seconds)** -> Power OFF
- UP** -> Increase Address
- DOWN** -> Decrease Address
- OK** -> Program Address
- UP & DOWN** -> Find Address
- DOWN** -> Escape from Program and Find operations

### TECHNICAL SPECIFICATIONS

OPERATING VOLTAGE	3.3V (DC)
CURRENT CHARGE	100 mA max.
CHARGE VOLTAGE	5 V (Mini USB)
CHARGE DURATION	4 hours min.
AUTO POWER OFF	After 2 minutes
MAX. HUMIDITY	95% RH Non-Condensing
OPERATING TEMPERATURE	0°C to 40°C
DIMENSIONS (PLASTIC)	86 (D) x 25 (H) mm
WEIGHT	172 g
<b>ORDER CODE</b>	
GFE-ZEOS-PROGRAMMER	PORTABLE PROGRAMMER