



EN54-3 Type B
CERTIFIED
1328-CPR-0300



VALKYRIE CS IP65

Conventional Wall Mount Sounder/ Beacon Outdoor Use-IP65

The VALKYRIE CS IP65 is a wall mounted Conventional Sounder/ Beacon with low power consumption. It is specifically designed to be used outdoors. Four different tones are available and selected using DIL switches 1 and 2.

Both continuous and pulsing outputs are provided via separate negative supply connections allowing for the presence of differentiated evacuation and alert sounds.

TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	20 V to 30 V DC
CURRENT - SOUNDER/ BEACON ACTIVE	10 mA - 280 mW @ 30 V DC
CURRENT - ALARM BEACON	1.4 mA
SOUNDER OUTPUT - CONTINUOUS	102 dB @ 1 m (Max.) - 97 dB @ 1 m (Min.)
SOUNDER OUTPUT - LOW FREQ.	103 dB @ 1 m (Max.) - 98 dB @ 1 m (Min.)
SOUNDER OUTPUT - HIGH FREQ.	110 dB @ 1 m (Max.) - 100 dB @ 1 m (Min.)
MAX. CABLE SIZE	2.5 mm ²
OPERATING TEMPERATURE	-20°C to 70°C
MAX. HUMIDITY	95% RH Non-Condensing
COLOUR / CASE MATERIAL	Red / ABS
PROTECTION CATEGORY	IP65 - Type B - Outdoor use
DIMENSIONS	112 (D) x 110 (H) mm inc. base
WEIGHT	315 g / 350 g - including packaging
ORDER CODE	
VALKYRIE CS	VALKYRIE CONVENTIONAL WALL SOUNDER - IP65 RATED
VALKYRIE CSB	VALKYRIE CONVENTIONAL WALL SOUNDER/ BEACON - IP65 RATED