



EN54-3 Type A  
CERTIFIED  
1328-CPR-0287



# VALKYRIE CS

## Conventional Wall Mount Sounder/ Beacon

The VALKYRIE CS is a wall mounted Conventional Sounder/ Beacon with low power consumption. Four different tones are available and selected using DIL switches 1 and 2.

Both continuous and pulsing outputs are provided via separate negative supply connections allowing for the presence of differentiated evacuation and alert sounds.

### TECHNICAL SPECIFICATIONS

SUPPLY VOLTAGE	20 V to 30 V DC
CURRENT - SOUNDER/ BEACON ACTIVE	10 mA - 280 mW @ 30 V DC
CURRENT - BEACON ACTIVE	1.4 mA
SOUNDER OUTPUT - CONTINUOUS	102 dB @ 1 m (Max.) - 97 dB @ 1 m (Min.)
SOUNDER OUTPUT - LOW FREQ.	103 dB @ 1 m (Max.) - 98 dB @ 1 m (Min.)
SOUNDER OUTPUT - HIGH FREQ.	110 dB @ 1 m (Max.) - 100 dB @ 1 m (Min.)
MAX. CABLE SIZE	2.5 mm <sup>2</sup>
OPERATING TEMPERATURE	-10°C to 55°C
MAX. HUMIDITY	95% RH Non-Condensing
COLOUR / CASE MATERIAL	Red or White / ABS
PROTECTION CATEGORY	IP21C - Type A - Indoor use
DIMENSIONS	110 (D) x 85 (H) mm inc. base
WEIGHT	254 g - inc. mounting base
<b>ORDER CODE</b>	
<b>VALKYRIE CS</b>	VALKYRIE CONVENTIONAL WALL SOUNDER
<b>VALKYRIE CSB</b>	VALKYRIE CONVENTIONAL WALL SOUNDER/ BEACON