



GFE-MCPE-C

Conventional Manual Call Point

The GFE-MCPE-C is a Conventional Manual Call Point, designed and manufactured to comply with EN54-11, compatible with all GFE Conventional Control panels. A bi-colour LED flashes Green when the unit is connected to a control panel and is illuminated Red when in Alarm.

The unit is supplied complete with a **hinged flap** which protects the trigger element from accidental activation and reduces malicious activations as **two actions** are required in order to activate the device. This unit can be both surface and flush mounted and it can be easily reset using the supplied key after activation.

TECHNICAL SPECIFICATIONS	
SUPPLY VOLTAGE	20-30 V DC
CURRENT - QUIESCENT	200 uA
CURRENT - DEVICE IN ALARM	50 mA @ 24 V DC - Alarm Resistance 470 Ohms Max.
CABLE SIZE	0.5-2.5 mm ²
COLOUR / CASE MATERIAL / IP PROTECTION	Red / ABS & Clear/ PC - Flame Retardant 94 V0 / IP24
OPER. TEMPERATURE	-10°C to 55°C
MAX. HUMIDITY	95% RH Non-Condensing
DIMENSIONS	92.6 (W) x 92.6 (H) x 60.1 mm
WEIGHT	152 g
ORDER CODE	
GFE-MCPE-C	CONVENTIONAL MANUAL CALL POINT